## Tipping Bucket Rain Gauge





Aerial view of Tipping Bucket Rain Gauge showing filter screen and funnel.

The Tipping Bucket Rain Gauge (Model TR-525) collects rainfall in an accurate and economical method. The rugged and reliable exterior of the unit allows it to be installed in the harshest of weather conditions and adverse climates. Being a completely automatic system, the unit is extremely easy to implement and use.

Methods of collecting rainfall data is simple as connecting the Tipping Bucket Rain Gauge to a data logger, event logger or a digital display and take the readings.

The rainfall sensor is dynamically calibrated in the factory and should not require re-calibration upon installation. Field maintenance should include occasional cleaning of the collector screen and inspection of the internal mechanism to make sure it is free from insects and debris. In some applications, user may need to occasionally verify and document sensor accuracy.

<b>₹</b> (🍆 5	peciti	cations

ITEM	DESCRIPTION	
Resolution	0.1 mm (0.01")	
Accuracy	1% at 25.4 mm/hour using dynamic calibration method.  1% at 1*/hour using dynamic calibration method.	
Switch Type	Magnetic Reed Switch	
Switch Closure	135 ms average	
Switch Rating	Maximum of 30 VDC @ 2A, 115 VAC @ 1A	
Temperature	1°C to 60°C (+32°F to + 122°F)	
Humidity	0 - 100%	
Height (with Mounting Feet)	25.4 cm (10.0°) (TR-525I) 30.48 cm (12.00°) (TR-525 M) 28.58 cm (11.25°) (TR-525 USW)	
Weight	2.5 lbs. (1.13 kg)	
Cable	60 ft, 2-conductor	
Receiving Orifice Diameter	16.8 cm (6.60°) (TR-525I - Imperial) 24.5 cm (9.66°) (TR-525M - Metric) 20.3 cm (8.00°) (TR-525 USW - Imperial)	
Funnel Depth	13.5 cm (5.3°) (TR-525I) 18.3 cm (7.2°) (TR-525 M) 16.3 cm (6.4°) (TR-525 USW)	
Tipping Bucket Material	Plastic	
Collector Funnel Material	Aluminum with gold anodized finish.	
Housing Material	Aluminum with white baked enamel finish.	



## **RST Instruments Ltd.**

11545 Kingston St., Maple Ridge, BC Canada V2X 0Z5

Telephone: 604 540 1100 Facsimile: 604 540 1005 Toll Free: 1 800 665 5599

info@rstinstruments.com

www.rstinstruments.com

## 🕳 applications

Accurately collect rainfall.

## 🌘 features

Exterior constructed of aluminum to withstand harsh weather conditions and climates.

Easily connects to data logger, event logger, or digital display.

Available in English (.01"/tip) or metric (.1mm/tip) measure.

Optional 8-inch collector is also available.

Completely automatic.

Dependable reed switch.

Debris screen prevents leaves and debris from entering unit.

Can easily convert from English to metric measure by simply changing the collector funnel.

The collector's knife-edge optimizes rainfall catch.

Hardened stainless steel pivot and jewel tipping assembly eliminates the need for bearings.

Three-year warranty.