




Locking Well Caps & Covers



RST Lockable Well Covers offer the ultimate in surface protection. Square design eliminates rotational removal while sturdy tabs allow security locks to be placed. The raised, angled lid allows casing to rise above the edge of the cover for increased access.

Flush Locking Well Plugs provide an easy and reliable way to create an air and water tight seal. Use of a padlock insures a tamper resistant plug, while printed warnings help prevent the possibility of contamination. Standard locking well plugs are available to fit 2 in. and 4 in. I.D. monitoring wells.

RST Bolt Down Welded Well Covers offer an economical way to provide traffic protection and help protect against water infiltration for monitor wells completed at grade. Each unit incorporates fully welded construction featuring a heavy duty steel skirt and 3/8 in. steel lid. A flat gasket is employed between the ring and cover as a water resisting seal. Two stainless steel bolts with nylon washers secure the lid in place.

ordering info

ITEM	PART #
2" J-Plug: Flush type lockable	EP2052
3" J-Plug: Flush type lockable	EP2053
4" J-Plug: Flush type lockable	EP2054
8" steel bolted Well Cover, powder coated	EP1305
8" steel bolted Well Cover, painted	EP1305A
8" round tamper resistant Well Cover, painted	EP1305A-T
6" round tamper resistant Well Cover, painted	EP1306-T
4" steel, square Well Cover, powder coated	EP1310
6" square, lockable Well Cover	EP1310B
4" square Well Cover, grey paint	EP1310A



RST Instruments Ltd.

11545 Kingston St.,
Maple Ridge, BC
Canada V2X 0Z5

Telephone: 604 540 1100
Facsimile: 604 540 1005
Toll Free: 1 800 665 5599

info@rstinstruments.com

www.rstinstruments.com

sealing well plug features

Petroleum and chemical resistant ESTALOC® plastic body, Buna-N/NBR O-ring and base washer.

Excellent O-ring memory in cold and hot temperatures.

Air and water tight seal.

Printed warning on top plate.

Die cast zinc latch assembly with yellow chromate coating and stainless steel roll pin.

Latch tapped for use with different size padlocks.

Low friction nylon thrust washer for easy tightening.

steel flush mount welded cover features

8 in. diameter, 3/8 in. thick steel lid and 10 gauge steel pipe with 8 in. diameter. (0.188 in. wall) pipe skirt as standard. Alternate sizes available upon request.

Leak resistant to prevent infiltration of water.

Warning label: "OBSERVATION MONITORING WELL DO NOT FILL" on each lid.

lockable above grade well cover features

4" square X 1/8 in. wall X 4 ft. size accommodates 2" well pipe and 2.75" inclinometer casing. Alternate sizes available upon request.

Warning label: "OBSERVATION MONITORING WELL DO NOT FILL" on each lid.